1/15






FIG. 1 communication system



3/15



4/15




FIG. 4 receiver automatic frequency control circuit





FIG. 5 radar and WLAN signals



7/15




FIG. 8 receiver with radar detection block

FIG. 9 radar detection logic

To Processor

9/15




FIG. 11 moving average determination logic

10/15




FIG. 12 state machine for detecting radar pulses







FIG. 13 method for determining if a radar pulse has been received







15/15

dar	method for performing radar detection processing	FIG. 18 meth	FIG	_
Z	>	×	3	<i>•</i>
¬	v	œ	Ø	bulse n
۵	0	z	Σ	y asiling
	¥	7	_	pulse 3
I	Ø	u.	ш)
۵	ပ	æ	∢	Salling Salling
fall time	pulse width	rise time	start time	

pulse interval quantity by type	- -	M - E	<u>-</u> ۵	W - W	
pulse inte	Lu Tu	- 2	En	n4	_
					_
pulse interval	4 - I	M – E	0 -	W-W	

pulse interval quantity by

pulse interval

E-A

7

E-A

<u>Ш</u>

2

<u>ш</u>

Ø-ŏ

7

Ø-Ø

_ _ ∑

n3

<u>-</u> N

Ø-₩

15

ტ |-|

FIG. 20° detection processing for extra pulses

FIG. 19 method for performing radar detection processing for missing pulses